

Category 6A (10G) Patch Cords



Description

Digi-Link P800 10G patch cord is yet another effort featuring a unique technology that makes cross talk between patch cords insignificant. These 10G patch cords provide the consistent signal transmission that is critical to performance of the entire system.

Our 10G patch cord delivers headroom beyond 800 MHz. The 10G Patch Cord is an assembly of special design of four pairs of highly flexible UTP cable, with a factory crimped and an expert assembly procedure terminated with RJ-45 connectors at both the ends thus delivering the best performance patch cord.

Qualifications and Approvals

- Jack mating life: 750 cycle.
- Jack pull force: 20 lbs (89)N.
- Jack contact force: 100 grams minimum.
- Retention force: 13 kgs minimum.

Benefits and Features

- ✓ Unique technology that makes cross-talk between patch cords insignificant.
- ✓ Plug Protection: Matching colored snag-less, elastomer Slim line boot
- ✓ Factory crimped & expert assembly procedure

Physical and Mechanical Properties

Voltage:	30 V
Current rating:	1.5 Amps
Contact Resistance:	20 mΩ max
Dielectric Strength:	1000V AC
Insulation Resistance:	≥ 500 mΩ
Connection:	8P 8C
Wiring:	23-26 AWG Stranded, Unshielded

Ordering Information

P/N	Description	Size	Weight Kg/Km	Wiring	Colour
DCTPCURJ01-GY	Cat 6A (10G) UTP Patch Cord	1m		EIA/TIA 568A/B	Grey
DCTPCURJ02-GY	Cat 6A (10G) UTP Patch Cord	2m		EIA/TIA 568A/B	Grey
DCTPCURJ03-GY	Cat 6A (10G) UTP Patch Cord	3m		EIA/TIA 568A/B	Grey